


1-Line, Bi-directional, Transient Voltage Suppressor



DFN0603-2L

Features

- Stand-off voltage: 3.3V Max
- Transient protection for each line according to
IEC61000-4-2(ESD): $\pm 30\text{kV}$ (contact)
IEC61000-4-5(surge): 8A (8/20 μs)
- Low leakage current
- Low clamping voltage
- RoHS Compliant

Applications

- Cellular handsets
- Tablets
- Laptops
- Network communication devices
- Other portable devices


Mechanical Data

- Package: DFN0603-2L
- Case Material: "Green" Molding Compound
- Marking Information: See Below
- Marking:

A3

■Definitions of electrical characteristics

V_{RWM} Reverse stand-off voltage
 I_R Reverse leakage current
 V_{BR} Reverse breakdown voltage
 V_{CL} Clamping voltage
 I_{PP} Peak pulse current





ESD3V3LZB1

■Maximum Ratings

PARAMETER	SYMBOL	Rating	UNIT
Peak pulse power ($t_p = 8/20\mu s$)	P_{pk}	80	W
Peak pulse current ($t_p = 8/20\mu s$)	I_{PP}	8	A
ESD according to IEC61000-4-2 air discharge	V_{ESD}	± 30	KV
ESD according to IEC61000-4-2 contact discharge		± 30	KV
Junction temperature	T_J	125	$^{\circ}C$
Storage temperature	T_{STG}	-55~150	$^{\circ}C$

■Electrical Characteristics ($T_a=25^{\circ}C$ Unless otherwise specified)

PARAMETER	Symbol	UNIT	Conditions	Min	Typ	Max
Reverse maximum working voltage	V_{RWM}	V				3.3
Reverse leakage current	I_R	nA	$V_{RWM} = 3.3 V$			500
Reverse breakdown voltage	V_{BR}	V	$I_{BR} = 1mA$	3.7		
Clamping voltage ³⁾	V_{CL}	V	$I_{PP} = 1A, t_p = 8/20\mu s$			7
		V	$I_{PP} = 8A, t_p = 8/20\mu s$			10
Junction capacitance	C_J	pF	$V_R = 0V, f = 1MHz$		16	

(1). TLP parameter: $Z_0 = 50\Omega$, $t_p = 100ns$, $t_r = 2ns$, averaging window from 60ns to 80ns. R_{DYN} is calculated from 4A to 16A.

(2). Contact discharge mode, according to IEC61000-4-2.

(3). Non-repetitive current pulse, according to IEC61000-4-5.

■Ordering Information (Example)

PREFERRED P/N	UNIT WEIGHT(mg)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
ESD3V3LZB1	Approximate 0.18	10000	100000	400000	Tape & reel



■ Characteristics (Typical)

Fig1. 8/20 μ s waveform per IEC61000-4-5




Fig2. Contact discharge current waveform per IEC61000-4-2




Fig3. Clamping voltage vs. Peak pulse current




Fig4. Capacitance vs. Reverse voltage




Fig5. Non-repetitive peak pulse power vs. Pulse time




Fig6. Power derating vs. Ambient temperature










Fig7. TLP Measurement






ESD3V3LZB1

■ Outline Dimensions



Type	Dimensions Unit mm		
	Min	Nom	Max
A	0.280	0.300	0.320
b	0.165	0.190	0.215
D	0.250	0.300	0.350
E	0.550	0.600	0.650
e		0.340	
L	0.205	0.230	0.255

■ Recommend land pattern



Unit:mm

Notes:

This recommended land pattern is for reference purposes only. Please consult your manufacturing group to ensure your PCB design guidelines are met



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.