


Schottky Barrier Diode



Features

- Moisture sensitivity level 1
- Reverse voltage: 40V
- Average forward current: 2A

Application

- Fast switching speed
- For general purpose switching applications

Mechanical data

- **Package:** DFN1608-2L
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102

■ Maximum Ratings ($T_a=25^{\circ}\text{C}$ Unless otherwise specified)

Parameter	Symbol	Unit	Value
Device marking code			2R
Repetitive peak reverse voltage	V_{RRM}	V	40
Forward current	I_F	A	2
Non-Repetitive Surge peak forward current @ t=8.3ms half-sine wave	I_{FSM}	A	10
Power Dissipation	P_D	mW	200
Junction temperature	T_J	$^{\circ}\text{C}$	-55 to +150
Storage temperature	T_{STG}	$^{\circ}\text{C}$	-55 to +150



MBR2040THG

RoHS
COMPLIANT

■ Electrical Characteristics (T_a=25°C Unless otherwise specified)

Parameter	Symbol	Unit	Conditions	Min	Typ	Max
Reverse voltage	V _R	V	I _R =100uA	40		
Forward Voltage	V _F	mV	I _F =100mA			380
			I _F =500mA			480
			I _F =1A			550
			I _F =2A			660
Reverse Leakage Current	I _R	uA	V _R =10V			5
			V _R =40V			30
Capacitance	C	pF	V _R =1V,f=1MHz			90
			V _R =10V,f=1MHz			40

■ Thermal Characteristics

Parameter	Symbol	Unit	Value
Thermal resistance, junction-to-ambient	R _{θJA} ⁽¹⁾	°C/W	500
Thermal resistance, junction-to-case	R _{θJC} ⁽¹⁾	°C/W	400

Note:

(1) Device mounted on PCB, single-sided copper, with standard footprint



■ Characteristics

Fig 1: P_D - T_a Curve




Fig 2: Capacitance Capability




Fig 3: Typical Forward Characteristics





Fig 4: Typical Reverse Characteristics






MBR2040THG

RoHS
COMPLIANT


■ Ordering Information

Preferred P/N	Packing Code	Unit Weight(g)	Minimum Package(pcs)	Inner Box Quantity(pcs)	Outer Carton Quantity(pcs)	Delivery Mode
MBR2040THG	F1	Approximate 0.0026	3000	30000	120000	Tape & Reel

■ Outline Dimensions



■ Suggested Pad Layout



UNIT: mm



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function, or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.